



# ***pac-mac***



**HGACBuy**  
THE SMART PURCHASING SOLUTION

Sourcewell  
Awarded Contract  
Contract # 042221-NUV

# **KB-20 SERIES**

## **BUILT WITH PRIDE IN THE USA**

The KB-20 is well-known for its quality, economic efficiency, durability, and user-friendly design. With various options for boom length and trailer capacity, this series is ideal for all loading applications.

This unit can be tailored to fit your specific needs.

**DO IT RIGHT with Pac-Mac!**



★★★★★  
**MADE IN THE USA**

**Visit us online at [www.e-pac-mac.com](http://www.e-pac-mac.com)**

Manufactured by Hol-Mac Corporation • P.O. Box 349 • Bay Springs, MS 39422 • 601-764-4121

# KB-20 SERIES

## TECHNICAL DATA & SPECIFICATIONS

### GENERAL SPECIFICATIONS

Height of boom to ground in lowest travel positions (based on 37 in. chassis height):	11 ft.
Boom length:	20 ft. (16 ft. with 4 ft. extension)
Boom rotation:	270° non-continuous
Lifting capacity at 20 ft. (with grapple):	3,387 lbs. (Standard) 4,500 lbs. (Optional) HD Series
H-Style Outriggers:	11 ft. 8in. (extended) 8 ft. (retracted)
Hydraulics:	Tandem pump allows simultaneous operations of multiple functions
Operator controls:	Greaseless mechanical levers or optional pilot-operated hydraulic joysticks

### BODY

Length:	18 ft. / 20 ft.
Capacity:	24 / 25 / 28 / 30 cubic yds.
Tilt:	45° +/- 1°
Floor:	3/16 in. (1/4 in. optional) 8 in. main sill 4 in. joist with 12 in. spacing
Sides:	Side ribs 24 in. spacing
Lighting:	L.E.D. with mid-body turn signal

### GRAPPLE

Width:	4 ft.
Fully open:	5 ft.

### LIFT CAPACITY

Radius:	
10 ft. radius:	7,172 lbs.
16 ft. radius:	4,682 lbs.
20 ft. radius:	3,387 lbs.

### STANDARD FEATURES:

#### Body

- Double "barn style" rear doors
- Complete discharge due to fully opening, swinging door(s)
- 45° body tilt for complete cleanout
- Nylon braided wiring harness
- Watertight connectors
- L.E.D. lighting

#### Grapple

- Low profile anti-scalp design
- High-strength tempered steel replaceable edges
- Dual cylinder configuration
- Easy to use when handling heavy, bulky materials
- Dual cylinders provide superior biting force

#### Boom/Pivot/Pedestal

- 20 ft. boom (16 ft. main boom, 4 ft. tip boom)
- Slewing ring and Gearbox configuration

#### Hydraulics

- All twin telescopic dump cylinders are designed with ductile iron gland/piston, chrome rods, and mounted outboard of frame
- Built-in holding valves for safety

#### Warranty

- 1-year hydraulic warranty
- 3-year structural warranty
- Best in the industry 3-year warranty on Gearbox and Slewing ring

#### Safety

- ANSI Z-245 compliance
- Bumper meets D.O.T. rear impact standards
- All hydraulic hoses are enclosed or shielded
- Integral holding valves in the main boom, tip boom, and outrigger cylinders
- Boom height alarm
- E-Stop located in operator's station

#### Outriggers

- Telescopic H-style
- Smooth pads for minimal street damage

### OPTIONS:

- Extended warranty available
- Hardox body
- Pilot-operated hydraulic joysticks
- Various tarp options
- Outrigger down alarm
- Outrigger-mounted strobes
- Additional light packages
- Body up alarm
- Frame-mounted toolbox
- Tool holder
- Door style option: single, double "barn style", or scow



POWERED BY:

**HOL-MAC**  
CORPORATION

Manufactured by Hol-Mac Corporation  
P.O. Box 349 • Bay Springs, MS 39422 • 601-764-4121  
Visit us online at [www.hol-mac.com](http://www.hol-mac.com)

