



pac-mac



HGACBuy
THE SMART PURCHASING SOLUTION

Sourcewell
Awarded Contract
Contract # 042221-NUV

LEAF VACUUM SYSTEM

THE ECONOMICAL SOLUTION FOR LEAF CHALLENGES

The Pac-Mac Leaf Collector is a self-contained leaf vacuum unit available chassis-mounted. This vacuum unit features a turbocharged diesel engine to meet your heavy-duty leaf and debris challenges with the performance and reliability you expect from Pac-Mac's product line. Variable body sizes and optional equipment let you tailor this unit to fit your operation needs. DO IT RIGHT with Pac-Mac!



★★★★★
MADE IN THE USA

Visit us online at www.e-pac-mac.com

Manufactured by Hol-Mac Corporation • P.O. Box 349 • Bay Springs, MS 39422 • 601-764-4121



pac-mac

LEAF VACUUM SYSTEM

TECHNICAL DATA & SPECIFICATIONS

CHASSIS-MOUNTED MODEL

Capacity:	25 yd ³
Container length:	156 in.
Drive Skid length:	75 in.
Unit weight:	10,500 lbs. 12,500 lbs.

CHASSIS-MOUNTED BODY CONSTRUCTION

Walls:	10 ga. side ribs / 26 in. spacing
Floor:	3/16 in. / 4 in. joists 26 in. spacing
Door:	Hydraulic top-hinged door
Lighting:	<ul style="list-style-type: none"> • D.O.T. compliant L.E.D. lighting • Dual oval strobe lights front and rear

CHASSIS-MOUNTED PERFORMANCE

Engine:	74 HP Diesel Tier 4
Engine controls:	On/start/off switch, throttle, RPM, oil pressure, temperature and safety shutdown in the event of low oil pressure or overheating
Impeller:	32 in. 6 blade constructed from high strength steel
Hydraulic drive:	Tandem hydraulic pump
Housing impeller liner:	Replaceable design
Hinged inlet door:	Quick access to impeller without removing the hose
Boom:	Curb-side mounted 12 ft., multi-directional
Controls:	All engine and hydraulic operations are controlled in the cab
Intake hose:	Wear resistant 16 in. diameter
Container dump:	52° tilt using two double acting dump cylinders



INSIDE LEAF VACUUM - DUAL STEERING CHASSIS

STANDARD FEATURES:

Body

- Self-contained for one person operation
- Proportional controls for smooth, precise boom movement
- Hydraulic drive offers a smooth engine to impeller direct connections without clutches or belt drives
- 10-micron return filtration
- Strobe lighting in front and rear
- Leaf container is vented towards the bottom, street side
- Removable vent screen covering for ease of cleaning
- Hydraulic single door
- Body props

Warranty

- 1-year hydraulic warranty
- 3-year structural warranty

Safety

- ANSI Z-245 compliance
- Bumper meets D.O.T. rear impact standards
- Container up alarm

OPTIONS:

- Rear view camera
- Rear door alarm
- Boom view camera
- Manufacture recommend dual steering chassis



POWERED BY:
HOL-MAC
CORPORATION

Manufactured by Hol-Mac Corporation
P.O. Box 349 • Bay Springs, MS 39422 • 601-764-4121
Visit us online at www.hol-mac.com

