



HGACBuy
THE SMART PURCHASING SOLUTION

RL SERIES

CARRIES THE LOAD OF THE SOLID WASTE INDUSTRY

World-class manufacturing combined with cutting-edge technology perfectly crafts a superior product: The Pac-Mac RL Series. The innovative RL Series is engineered using the most advanced computer modeling systems. The Pac-Mac RL Series proves that Pac-Mac is committed to providing the highest quality products in the solid waste industry and can be mounted on a non-CDL chassis.

DO IT RIGHT with Pac-Mac!



MADE IN THE USA

Visit us online at www.e-pac-mac.com

Manufactured by Hol-Mac Corporation • P.O. Box 349 • Bay Springs, MS 39422 • 601-764-4121



RL SERIES

TECHNICAL DATA & SPECIFICATIONS

MODEL

	RL6	RL8	RL10
Capacity:	6 yd ³	8 yd ³	10 yd ³
Hopper capacity:	1 yd ³	1 yd ³	1 yd ³
Body weight (body shell only):	2,537 lbs.	2,917 lbs.	3,391 lbs.
Body weight (complete unit, less option):	7,235 lbs.	7,680 lbs.	8,120 lbs.
Hopper inside width:	66.3 in.	66.3 in.	66.3 in.

BODY SPECIFICATIONS

	RL6	RL8	RL10
Sidewalls (curved shell):	10 ga. high tensile steel	10 ga. high tensile steel	10 ga. high tensile steel
Flat floor (single sheet):	7 ga. high tensile steel	7 ga. high tensile steel	7 ga. high tensile steel
Roof (curved shell):	10 ga. high tensile steel	10 ga. high tensile steel	10 ga. high tensile steel
Ejector panel face:	10 ga. high tensile steel	10 ga. high tensile steel	10 ga. high tensile steel
Hopper:	3/16 in. 100 ksi T-1 (1/4 in. T-1 option)	3/16 in. 100 ksi T-1 (1/4 in. T-1 option)	3/16 in. 100 ksi T-1 (1/4 in. T-1 option)
Packer panel face:	3/16 in. T-1 steel	3/16 in. T-1 steel	3/16 in. T-1 steel
Slide panel face:	3/16 in. high tensile steel	3/16 in. high tensile steel	3/16 in. high tensile steel
Hopper sides:	3/16 in. T-1 steel (lower tailgate); 10 ga. high tensile steel (upper tail gate)	3/16 in. T-1 steel (lower tailgate); 10 ga. high tensile steel (upper tail gate)	3/16 in. T-1 steel (lower tailgate); 10 ga. high tensile steel (upper tail gate)

HYDRAULIC SYSTEM

	RL6	RL8	RL10
Cylinders:			
Ejector:	Single-stage 4.5 in. bore	2-stage 4.5 in. bore	2-stage 4.5 in. bore
Tailgate:	(2) 3.5 in. bore; 2 in. rod; 20 in. stroke	(2) 3.5 in. bore; 2 in. rod; 20 in. stroke	(2) 3.5 in. bore; 2 in. rod; 20 in. stroke
Slide:	(2) 3.5 in. bore; 2 in. rod; 19 in. stroke	(2) 3.5 in. bore; 2 in. rod; 19 in. stroke	(2) 3.5 in. bore; 2 in. rod; 19 in. stroke
Packer:	(2) 3.5 in. bore; 2 in. rod; 19 in. stroke	(2) 3.5 in. bore; 2 in. rod; 19 in. stroke	(2) 3.5 in. bore; 2 in. rod; 19 in. stroke
Valves:			
Shutoff:	Ball	Ball	Ball
Packing controls:	Sectional spool	Sectional spool	Sectional spool
Ejector/tailgate raise:	Sectional spool	Sectional spool	Sectional spool
Operating pressure in PSI:	2,400	2,400	2,400
Maximum operating pressure:	2,700	2,700	2,700
Gallons per minute (GPM):	21 GPM	21 GPM	21 GPM
Reservoir:	30 gal.	30 gal.	30 gal.
Packing cycle time:			
Complete:	15-17 sec.	15-17 sec.	15-17 sec.
Reload:	3 sec.	3 sec.	3 sec.
Compaction rate in lb./yd.:	700-800	700-800	700-800

STANDARD FEATURES:

Body

- One piece flat floor
- Curved shell body
- Fast cycle time
- Wide open accessibility for cleaning and maintenance
- Automatic latches and integrated tailgate props
- The industry's highest standard for hydraulic cleanliness
- L.E.D. lighting, weatherproof connections and braided loom
- Dual amber oval rear strobes
- Heat-treated pins and replaceable bushings throughout
- Sectional valves
- Slide and Packer cylinders are interchangeable

Warranty

- 1-year major structural component parts
- 1-year non-hydraulic replacement parts

Safety

- Meets or exceeds ANSI Z-245
- Large access door with safety interlock
- Emergency stop on curb side
- Driver alert buttons on both side

OPTIONAL EQUIPMENT:

- Single cart tipper
- Container winch (minimum chassis height 37 in.)
- Kick bar with latches (minimum chassis height 37 in.)
- Additional strobe light packet
- Amber oval flush mount strobes (front/rear)
- Rear vision camera
- Work lights over hopper and tailgate sides
- Frame mounted tool box
- Tool holder on body
- Emergency stop on street side
- Hyper Hopper adds .75 yd³ (34 in. max chassis height only)



POWERED BY:

HOL-MAC
CORPORATION

Manufactured by Hol-Mac Corporation
P.O. Box 349 • Bay Springs, MS 39422 • 601-764-4121
Visit us online at www.hol-mac.com



All designs, specifications, and components are subject to change at the manufacturer's sole discretion at any time without notice. Data published herein is for informational purposes only and shall not be construed to warrant suitability of the unit for any particular purpose, as performance may vary with the conditions encountered. The only warranty is our standard written warranty for this product at the time of shipment.