pac-mac

HGACBuy THE SMART PURCHASING SOLUTION

npp gov

Sourcewell
Awarded Contract
Contract # 010825-HMC

KB-220 SERIES

HERE COMES THE BOOM

The KB-220 functions in solid waste, tree care, and the forestry industry, with a boom reach of up to 25 feet. This unit comes standard with hydraulic joysticks and a tandem pump for even smoother operation. The KB-220 is quality built with pride.
DO IT RIGHT with Pac-Mac!

MADE IN THE USA

Visit us online at www.e-pac-mac.com

Manufactured by Hol-Mac Corporation • P.O. Box 349 • Bay Springs, MS 39422 • 601-764-4121

KB-220 SERIES

TECHNICAL DATA & SPECIFICATIONS

GENERAL SPECIFICATIONS

Height of boom to ground in lowest travel positions (based on 42 in. chassis height):	12 ft. 6 in.
Boom length:	20 ft. fixed / 22 ft. fixed
Optional boom length:	23 ft. (20 ft. with 3ft. extension) 25 ft. (22 ft. with 3ft. extension)
Boom rotation:	270° non-continuous
Litfting capacity at 20 ft. (with grapple):	5,963 lbs.
Hydraulics:	Tandem pump allows simultaneous operations of multiple functions
Operator controls:	Pilot-operated hydraulic joysticks

BODY

Length:	20 ft. / 22 ft.
Capacity:	30 / 40 cubic yds.
Tilt:	45° +/- 1°
Floor:	3/16 in. (1/4 in. optional) 4 in. joist with 12 in. spacing
Sides:	Side ribs 24 in. spacing
Lighting:	L.E.D. with mid-body turn signal

GRAPPLE

Width:	4 ft.
Fully Open:	5 ft.

LIFT CAPACITY

Radius:	
10 ft. radius:	11,794 lbs.
15 ft. radius:	7,707 lbs.
20 ft. radius:	5,963 lbs.

STANDARD FEATURES:

Body
- Double "barn style" rear doors
- Complete discharge due to fully opening, swinging door(s)
- 45° body tilt for complete cleanout
- Nylon braided wiring harness
- Watertight connectors
- L.E.D. lighting

Grapple
- Low profile anti-scalp design
- High-strength tempered steel replaceable edges
- Dual cylinder configuration
- Easy to use when handling heavy, bulky materials
- Dual cylinders provide superior biting force

Boom/Pivot/Pedestal
- 23 ft. boom (20 ft. main/tip boom with 3 ft. extend boom) or 25 ft. boom (22 ft. main/tip boom with 3 ft. extend boom)
- Pilot-operated hydraulic joysticks
- Slewing ring and Gearbox configuration

Hydraulics
- All twin telescopic dump cylinders are designed with ductile iron gland/piston, chrome rods, and mounted outboard of frame
- Built-in holding valves for safety

Warranty
- 1-year hydraulic warranty
- 3-year structural warranty
- Best in the industry 3-year warranty on Gearbox and Slewing ring

Safety
- ANSI Z-245 compliance
- Bumper meets D.O.T. rear impact standards
- All hydraulics hoses are enclosed or shielded
- Integral holding valves in the main boom, tip boom, and outrigger cylinders
- Boom height alarm
- E-Stop located in operator's station

Outriggers
- A-style design with easy removal
- Smooth pads for minimal street damage

OPTIONS:

- Extended warranty available
- Hardox Body
- Rotating operating station "crowsnest" allows 360° rotation
- Various tarp options
- Outrigger down alarm
- Outrigger-mounted strobes
- Additional light packages
- Body up alarm
- Frame-mounted toolbox
- Tool holder
- Door style option: single, double "barn style", or scow

POWERED BY:
HOL-MAC CORPORATION
Manufactured by Hol-Mac Corporation
P.O. Box 349 • Bay Springs, MS 39422 • 601-764-4121
Visit us online at www.hol-mac.com

All designs, specifications, and components are subject to change at the manufacturer's sole discretion at any time without notice. Data published herein is for informational purposes only and shall not be construed to warrant suitability of the unit for any particular purpose, as performance may vary with the conditions encountered. The only warranty is our standard written warranty for this product at the time of shipment.

3.0_06012026