



# ***pac-mac***



**HGACBuy**  
THE SMART PURCHASING SOLUTION

Sourcewell  
Awarded Contract  
Contract # 042221-NUV

# **KB-2 SERIES**

## **THE NON-CDL SOLUTION LOADER**

The KB-2 is the non-CDL solution in the Pac-Mac Grapple Truck Series. The KB-2 is known for its quality, user-friendly design, economic efficiency, and capability to handle various public works and solid waste industry obstacles.

DO IT RIGHT with Pac-Mac!



\*\*\*\*\*  
\*\*\*\*\*  
**MADE IN THE USA**

**Visit us online at [www.e-pac-mac.com](http://www.e-pac-mac.com)**

Manufactured by Hol-Mac Corporation • P.O. Box 349 • Bay Springs, MS 39422 • 601-764-4121



**pac-mac**

# KB-2 SERIES

## TECHNICAL DATA & SPECIFICATIONS

### GENERAL SPECIFICATIONS

Height of boom to ground in lowest travel positions (based on 37 in. chassis height):	11 ft.
Boom length:	17 ft.
Boom rotation:	270° non-continuous
Lifting capacity at 17 ft. (with grapple):	2,625 lbs.
Fixed H-style Outriggers:	8 ft.
Hydraulics:	Tandem pump allows simultaneous operations of multiple functions
Operator controls:	Greaseless mechanical levers or optional pilot-operated hydraulic joysticks

### BODY

Length:	18 ft.
Capacity:	20 cubic yds.
Tilt:	45° +/- 1°
Floor:	3/16 in. 8 in. main sill 4 in. joist with 16 in. spacing
Sides:	4 ft. wall body 1/8 in. Hardox with built in dirt guard
Lighting:	L.E.D. with mid-body turn signal

### GRAPPLE

Width:	30 in.
Fully open:	5 ft.

### LIFT CAPACITY

Radius:	
10 ft. radius:	6,020 lbs.
*16 ft. radius:	3,025 lbs.
17 ft. radius:	2,625 lbs.

\*Compared to the competition

### STANDARD FEATURES:

#### Body

- Hardox
- Double "barn style" rear doors
- Complete discharge due to fully opening, swinging door(s)
- 45° body tilt for complete cleanout
- Nylon braided wiring harness
- Watertight connectors
- L.E.D. lighting

#### Grapple

- Low profile anti-scalp design
- High-strength tempered steel replaceable edges
- Dual cylinder configuration
- Easy to use when handling heavy, bulky materials
- Dual cylinders provide superior biting force

#### Boom/Pivot/Pedestal

- 17 ft. boom (10 ft. main boom, 7 ft. tip boom)
- Slewing ring and Gearbox configuration

#### Hydraulics

- All twin telescopic dump cylinders are designed with ductile iron gland/piston, chrome rods, and mounted outboard of frame
- Built-in holding valves for safety

#### Warranty

- 1-year hydraulic warranty
- 3-year structural warranty
- Best in the industry 3-year warranty on Gearbox and Slewing ring

#### Safety

- ANSI Z-245 compliance
- Bumper meets D.O.T. rear impact standards
- All hydraulic hoses are enclosed or shielded
- Integral holding valves in the main boom, tip boom, and outrigger cylinders
- Boom height alarm
- E-Stop located in operator's station

#### Outriggers

- Fixed H-style
- Smooth pads for minimal street damage

### OPTIONS:

- Extended warranty available
- Pilot-operated hydraulic joysticks
- Various tarp options
- Outrigger down alarm
- Outrigger-mounted strobes
- Additional light packages
- Body up alarm
- Frame-mounted toolbox
- Tool holder
- Single door



POWERED BY:

**HOL-MAC**  
CORPORATION

Manufactured by Hol-Mac Corporation  
P.O. Box 349 • Bay Springs, MS 39422 • 601-764-4121  
Visit us online at [www.hol-mac.com](http://www.hol-mac.com)



All designs, specifications, and components are subject to change at the manufacturer's sole discretion at any time without notice. Data published herein is for informational purposes only and shall not be construed to warrant suitability of the unit for any particular purpose, as performance may vary with the conditions encountered. The only warranty is our standard written warranty for this product at the time of shipment.